

NG CASTORE PRO

Membrane Nitrogen generator
electronic controlled

The NitroGen series **CASTORE PRO** are Membrane Nitrogen Generators. They are engineered to transform standard compressed air into a safe, regulated supply of Nitrogen with a purity up to 99.5%. An optional channel can provide up to 45 L/min of compressed, dry and regulated air.

The exclusive electronic flow control allows to generate Nitrogen with a higher purity using a smaller volume of air which results in reduced energy costs and maintenance of any external compressor. Continuous control of the operating parameters allows to maintain the system at its maximum efficiency.

The CASTORE PRO with it's dual Nitrogen and Air outlets has been developed to meet specific requirements in term of gas, flow, purity and pressure in LC-MS applications. It can be used for the evaporation of solvents in samples being analysed.

- Compatible with all LCMS
- Dual Nitrogen and Air generator
- Low noise
- Low maintenance
- Generates nitrogen on demand
- Exclusive electronic flow control
- Designed to run 24 hours a day



Smart **Gas** Generators



Specifications

Models: NG CASTORE PRO	25	25-40	45	45-40	60
N2 outlet					
Flow rate (Max)	25 l/min		45 l/min		60l/min
Outlet pressure (min; Max)	2.0 bars; Inlet pressure – 1.0 bar				
Nitrogen purity (Inlet Pressure > 8 bar)	> 98.5 % @ 25 l/min > 99.5 % @ 10 l/min		> 98.5 % @ 45 l/min > 99.5 % @ 25 l/min		> 98.5 % @ 60 l/min
Dry Air outlet					
Flow rate (Max)	-	40 l/min	-	40 l/min	-
Outlet pressure	-	Inlet pres. - 1.0bar	-	Inlet pres. - 1bar	-
Dew point	-	< -20°C (-4°F)	-	< -20°C (-4°F)	-
Air inlet					
Air inlet requirement	Particulate: <1 micron Dewpoint: < 20°C (68°F) Oil: <0.01 mg/m ³				
Flow rate (Max)	100 l/min	155 l/min	160 l/min	215 l/min	200 l/min
Supply pressure (min; Max)	5 bars; 10bars				
Temperature (min; Max)	1°C (34°F); 45°C(113°F)				
Communication					
LCD with touch screen	Standard				
RS485	Standard				
RS232	For service				
General data					
Supply rating	100-240Vac 50/60Hz – 1A				
Connection type	IEC320-C13				
Installation power (max)	25W (30VA)				
Fuse rating	2 x 1A -240Vac (5x20mm)				
Net weight	<23 kg		<25 kg		
Dimensions (W x D x H) mm	260 x 280 x 1200				
Connections					
N2 outlet port	¼" BSPP female				
Dry Air outlet port	¼" BSPP female				
Inlet port	¼" BSPP female				
Drain port	¼" BSPP female				
Operating/storage conditions					
Temperature	5-35°C (41-95°F)				
Humidity (max, non condensing)	80% at 25°C (77°F)				
Noise	<25dB(A)				
IP rating	IP20				
Pollution degree rating	2 (with no aromatic compounds)				
Altitude	< 2000m				

Main applications

- LC-MS
- Solvent evaporation

Smart Gas Generators



LNI-GGI srl con socio unico
www.lni-swissgas.eu

Registered office: Via Sassoferato 1, 20135 Milano MI
Logistics centre: Via E. Mattei 9, 35038 Torreglia PD